

JAGUAR		980	970	960	950	940	930
Engine							
Manufacturer		MAN	MAN	Mercedes-Benz	Mercedes-Benz	Mercedes-Benz	Mercedes-Benz
Type		D2862	D2868	OM 473 LA	OM 473 LA	OM 471 LA	OM 471 LA
Cylinders		V12	V8	S6	S6	S6	S6
Displacement	l	24.24	16.16	15.6	15.6	12.8	12.8
Engine output at working speed of 1700 rpm (ECE R 120)	kW/hp	650/884 ¹	570/775 ¹	460 / 626	430 / 585	380/516	340 / 462
Fuel tank with auxiliary tank	l	1200 + 300 ¹	1200 + 300 ¹	1050 + 300	1050 + 300	1050 + 300	1050 + 300
Urea tank	l	– ¹	– ¹	130	130	130	130
Fuel consumption measurement		o	o	o	o	o	o
DYNAMIC POWER		o	o	o	o	o	–
Running gear							
Traction drive: 2-speed OVERDRIVE transmission, automatic (hydrostatic)		●	●	●	●	●	●
Differential lock		o	o	o	o	o	o
Tyre pressure adjustment system - drive axle		o	o	o	o	o	o
Tyre pressure adjustment system - drive and steering axle		o	o	o	o	o	o
Steering axle, standard		o	o	o	o	o	o
Steering axle, 3 x adjustment, 2510, 2970, 3130 mm		o	o	o	o	o	o
POWER TRAC driven steering axle		o	o	o	o	o	o
Water / silage additive tank content, 375 l		●	●	●	●	●	●
ACTISILER 20 content, highly concentrated, 20 l	l	o	o	o	o	o	o
Front attachments							
Maize front attachment ORBIS, RU (rows / width)	r/m	12 / 9, 10 / 7.5, 8 / 6	12 / 9, 10 / 7.5, 8 / 6	12 / 9, 10 / 7.5, 8 / 6	10 / 7.5, 8 / 6, 6 / 4.5	10/7.5, 8/6, 6 /4.5	8 / 6, 6 / 4.5
PICK UP 380, 300, working width 3600, 2620 mm		o	o	o	o	o	o
DIRECT DISC 610, 520, working width 5995, 5125 mm		o	o	o	o	o	o
DIRECT DISC 600/500, working width 5960, 5130 mm		o	o	o	o	o	o
Front attachment drive							
Standard		●	●	●	●	●	●
Split-power		o	o	o	o	o	o
Variable		o	o	o	o	o	o
Intake							
Width, 730 mm		●	●	●	●	●	●
Intake and precompression rollers, no. 4		●	●	●	●	●	●
COMFORT CUT chop length adjustment, infinitely variable		●	●	●	●	●	●
Chopping cylinder							
Width, 750 mm		●	●	●	●	●	●
Diameter, 630 mm		●	●	●	●	●	●
Knife configuration							
V20 / 2 x 10		o	o	o	o	o	o
V10 / 2 x 5							
V24 / 2 x 12		o	o	o	o	o	o
V12 / 2 x 6							
V28 / 2 x 14		o	o	o	o	o	o
V14 / 2 x 7							
V36 / 2 x 18		o	o	o	o	o	o
V18 / 2 x 9							
V12 / 2 x 6							
Automatic knife sharpening from cab		●	●	●	●	●	●
Shear bar adjusted automatically from the cab		●	●	●	●	●	●
MULTI CROP CRACKER							
MCC CLASSIC, M, ø 196 mm		–	–	o	o	o	o
MCC CLASSIC, L, ø 250 mm		o	o	o	o	–	–
MCC MAX, ø 265 mm		o	o	o	o	–	–
MCC SHREDLAGE, M, ø 196 mm		–	–	o	o	o	o
MCC SHREDLAGE, L, ø 250 mm		o	o	o	o	–	–

¹ As the engine output is greater than 560 kW, the JAGUAR 980 and 970 models are not subject to any emission regulations.

● Standard ○ Option □ Available – Not available

JAGUAR		980	970	960	950	940	930
Crop accelerator							
Width 680 mm		●	●	●	●	●	●
Diameter 540 mm		●	●	●	●	●	●
Gap setting 2-10 mm		o	o	o	o	o	o
Discharge spout							
Breakback protection		●	●	●	●	●	●
Swivel angle, standard, 210°		●	●	●	●	●	●
Swivel angle with OPTI FILL / AUTO FILL, 225°		o	o	o	o	o	o
Discharge spout S (up to DD 250)		●	●	●	●	●	●
Extension M (ORBIS 600), 1 x 750 mm		o	o	o	o	o	o
Extension L (ORBIS 750), 2 x 750 mm		o	o	o	o	o	o
Extension XL (ORBIS 900), 3 x 750 mm		o	o	o	o	o	o
EASY							
OPTI FILL, optimised spout control		o	o	o	o	o	o
AUTO FILL, automatic trailer filling		o	o	o	o	o	o
STOP ROCK stone detector		o	o	o	o	o	o
QUANTIMETER throughput measurement		o	o	o	o	o	o
QUANTIMETER + continuous moisture measurement		o	o	o	o	o	o
Job management		o	o	o	o	o	o
Yield mapping		o	o	o	o	o	o
TELEMATICS		o	o	o	o	o	o
AUTO PILOT central sensors (maize)		o	o	o	o	o	o
CAM PILOT swath recognition (grass)		o	o	o	o	o	o
GPS PILOT		o	o	o	o	o	o
CRUISE PILOT		●	●	●	●	●	●
Maintenance							
Central lubrication, 16-l grease reservoir		o	o	o	o	o	o
Service lighting		o	o	o	o	o	o
VISTA CAB							
A / C MATIC air conditioning		o	o	o	o	o	o
CEBIS colour monitor		●	●	●	●	●	●
Printer		o	o	o	o	o	o
Comfort seat		o	o	o	o	o	o
Swivelling seat		o	o	o	o	o	o
Premium seat, ventilated, heated		o	o	o	o	o	o
Leather seat, ventilated, heated		o	o	o	o	o	o
Passenger seat		o	o	o	o	o	o
Basic machine without front attachment							
Working length	mm	6495	6495	6495	6495	6495	6495
Working height with discharge spout extension XL	mm	6335	6335	6335	6335	6335	6335
Transport height	mm	3945	3945	3945	3945	3945	3945
Transport length with discharge spout extension XL	mm	8590	8590	8590	8590	8590	8590
Weight on standard tyres without front attachment	kg	13800	13400	13150	13150	12750	12750

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual. All technical specifications relating to engines are based on the European emission regulation standards: Stage. Any reference to the Tier standards in this document is intended solely for information purposes and ease of understanding. It does not imply approval for regions in which emissions are regulated by Tier.

● Standard ○ Option □ Available – Not available

JAGUAR		980	970	960	950	940	930
--------	--	-----	-----	-----	-----	-----	-----

Tyres

Drive axle, transport width acc. to tyre size up to 1950 mm diam.

680/85 R 32	mm	3130	3130	3130	3130	3130	3130
IF 680/85 R 32 179 A8	mm	3130	3130	3130	3130	3130	3130
710/70 R 38 TR	mm	3172	3172	3172	3172	3172	3172
710/70 R 38 171 D	mm	3172	3172	3172	3172	3172	3172
710/75 R 34 MI	mm	3172	3172	3172	3172	3172	3172
710/75 R 34 178 A8	mm	3172	3172	3172	3172	3172	3172
800/70 R 32 175 A8	mm	3299	3299	3299	3299	3299	3299
800/70 R 32 181 A8 MI	mm	3299	3299	3299	3299	3299	3299
IF 800/70 R 32 182 A8 MI	mm	3299	3299	3299	3299	3299	3299
IF 800/70 R 32 182 A8 (for extended machine width)	mm	3380	3380	3380	3380	3380	3380
900/60 R 32 176 A8	mm	3490	3490	3490	3490	3490	3490
900/60 R 32 176 A8 MI	mm	3490	3490	3490	3490	3490	3490
900/60 R 32 176 A8 TR	mm	3490	3490	3490	3490	3490	3490

Drive axle, transport width acc. to tyre size up to 2050 mm diam.

710/70 R 42	mm	3180	3180	3180	3180	3180	3180
800/70 R 38	mm	3299	3299	3299	3299	3299	3299
800/70 R 38 (for extended machine width)	mm	3380	3380	3380	3380	3380	3380
900/60 R 38 178 D	mm	3490	3490	3490	3490	3490	3490

Steering axle, transport width by tyre size

VF 520/80 R 26	mm	2920	2920	2920	2920	2920	2920
540/65 R 28	mm	2960	2960	2960	2960	2960	2960
540/65 R 30	mm	2960	2960	2960	2960	2960	2960
600/65 R 28 TR	mm	3050	3050	3050	3050	3050	3050
600/65 R 28	mm	3050	3050	3050	3050	3050	3050
VF 620/70 R 26	mm	3040	3040	3040	3040	3040	3040
620/70 R 30	mm	3060	3060	3060	3060	3060	3060